



UNIVERSITI PUTRA MALAYSIA

**CONTINUOUS PRODUCTION OF ORGANIC ACIDS FROM PALM OIL
MILL EFFLUENT AND KITCHEN GARBAGE**

PHANG LAI YEE

FSMB 2001 26

**CONTINUOUS PRODUCTION OF ORGANIC ACIDS FROM PALM OIL
MILL EFFLUENT AND KITCHEN GARBAGE**

By

PHANG LAI YEE

**Thesis Submitted in Fulfilment of the Requirement for the Degree of
Master of Science in the Faculty of Food Science and Biotechnology
Universiti Putra Malaysia**

February 2001



Specially dedicated to,

**My beloved parents, sisters, friends
and Kum Cheng,**

**For their invaluable love, sacrifices,
and wishing me all the best.....**

Abstract of thesis presented to the Senate of Universiti Putra Malaysia in
fulfilment of the requirement for the degree of Master of Science

**CONTINUOUS PRODUCTION OF ORGANIC ACIDS FROM PALM OIL
MILL EFFLUENT AND KITCHEN GARBAGE**

By

PHANG LAI YEE

February 2001

Chairman: Associate Professor Dr. Mohd. Ali Hassan

Faculty: Food Science and Biotechnology

Waste materials such as palm oil mill effluent (POME) and kitchen garbage or refuse can be used as raw materials for organic acids production. In this study, POME and blended kitchen garbage were separately fed continuously into an anaerobic fermentation system in which they were converted to organic acids namely acetic, propionic, butyric and lactic acids, depending on the experimental conditions and type of microorganisms involved in the anaerobic treatment.

The effect of two types of neutralizer, CaCO_3 and NaOH , on anaerobic treatment of POME was examined. The POME treatment was stabilized at pH 5.0-5.5 when CaCO_3 was used to adjust the pH. Subsequently, anaerobic treatment of POME was performed at pH 5.0-5.5 with sludge recycle system. The major organic acids produced were acetic (5.0-5.6 g/L), propionic (2.0-2.6 g/L) and butyric acids (2.3-3.3 g/L). Higher amount of butyric acid (average 2.8 g/L) was produced at pH 5.0. The sludge solids in the treated POME were separated by freezing-thawing technique and recycled into the reactor. More than 87% of the suspended solids in the treated POME were removed by this method. However, the clarified solution



still contained more than 20,000 mg/L of total solids. Total microbial population stabilized at 10^8 cfu/mL in the reactor but reduced to 10^6 cfu/mL in the dewatered sludge upon freezing and thawing. The organic acids were fractionated to obtain more concentrated organic acids (22.4 g/L).

In the case of kitchen garbage, *Lactobacillus rhamnosus* converted the carbohydrates to lactic acid with more than 87% selectivity. Glucoamylase with the activity of 60 U/mg was added during the fermentation at a dosage of 300 mg/L to enhance the hydrolysis of organic materials. Three sets of experimental conditions were studied, i.e. at pH 6.8 with RT 5 days, pH 5.5 with RT 5 days and pH 5.5 with RT 2.5 days which produced an average lactic acid concentration of 42 g/L, 53 g/L and 50 g/L respectively. The residual glucose and total sugars at steady state were less than 1 g/L and 20 g/L respectively. The optical purity of L-lactic acid obtained was more than 90% under the optimum condition of pH 5.5 with RT 2.5 days.

Abstrak thesis yang dikemukakan kepada Senat Universiti Putra Malaysia sebagai memenuhi keperluan untuk ijazah Master Sains.

**PENGHASILAN ASID ORGANIK SECARA BERTERUSAN DARI
EFLUEN KILANG KELAPA SAWIT DAN BAHAN BUANGAN DAPUR**

Oleh

PHANG LAI YEE

Februari 2001

Pengerusi: Profesor Madya Dr. Mohd. Ali Hassan

Fakulti: Sains Makanan dan Bioteknologi

Bahan sisa seperti efluen kilang kelapa sawit (POME) dan sisa makanan dari dapur boleh menjadi bahan mentah untuk penghasilan asid organik. Dalam kajian ini, POME dan sisa makanan dari dapur yang telah dihancurkan disuapkan secara berterusan ke dalam sistem anaerobik di mana bahan sisa tersebut ditukar kepada asid organik seperti asid asetik, propionik, butirik dan laktik, bergantung kepada keadaan ujikaji dan jenis mikroorganisma yang terlibat dalam rawatan anaerobik tersebut.

Kesan bahan penimbal (CaCO_3 dan NaOH) terhadap rawatan anaerobik POME telah dikaji. Rawatan POME mencapai kestabilan pada pH 5.0-5.5 apabila CaCO_3 digunakan untuk mengawal pH. Seterusnya, rawatan POME dijalankan pada pH 5.0-5.5 dengan sistem kitar semula sisa enapcemar. Asid organik utama yang dihasilkan ialah asid asetik (5.0-5.6 g/L), propionik (2.0-2.6 g/L) dan butirik (2.3-3.3 g/L). Jumlah asid butirik yang dihasilkan pada pH 5.0 adalah lebih tinggi, iaitu 2.8 g/L (purata). Pepejal sisa enapcemar dipisahkan dari POME terawat dengan

mengguna teknik penyejukbekuan diikuti oleh pencairan. Teknik ini telah dapat memisahkan lebih daripada 87% bahan terampai dari POME yang dirawat. Walau bagaimanapun, larutan cairan masih mengandungi lebih daripada 20,000 mg/L bahan pepejal. Populasi mikroorganisma dalam reaktor mencapai kestabilan pada 10^8 unit koloni terbentuk/mL tetapi populasi mikroorganisma dalam sisa enapcemar (untuk dikitar semula) menurun ke 10^6 unit koloni terbentuk/mL selepas penyejukbekuan dan pencairan. Pembahagian asid organik dilakukan untuk memekatkan asid organik kepada 22.4 g/L.

Untuk sisa makanan dari dapur, *Lactobacillus rhamnosus* menukarkan karbohidrat dalam sisa dapur kepada asid laktik dengan daya pemilihan melebihi 87%. Glukoamilase yang berkepekatan 300mg/L digunakan semasa fermentasi untuk menggalakkan penguraian bahan organik. Tiga keadaan ujikaji telah dijalankan semasa fermentasi itu pada pH 6.8 dengan 5 hari masa tahanan, pH 5.5 dengan masa tahanan 5 hari dan pH 5.5 dengan 2.5 hari masa tahanan. Kepekatan purata asid laktik masing-masing ialah 42 g/L, 53 g/L dan 50 g/L. Baki kandungan glukosa dan jumlah gula adalah kurang daripada 1 g/L dan 20 g/L masing-masing. Ketulenan optikal L-asid laktik yang dicapai melebihi 90% pada keadaan optima, iaitu pada pH 5.5 dengan masa tahanan 2.5 hari.

ACKNOWLEDGEMENTS

I wish to express my deepest appreciation and sincere gratitude to my supervisor, Associate Prof. Dr. Mohd. Ali Hassan and members of the supervisory committee Prof. Dr. Mohamed Ismail Abdul Karim and Associate Prof. Dr. Arbakariya bin Ariff, for their untiring and invaluable guidance, comments and suggestions throughout the project. My sincere thanks to Associate Prof. Dr. Yoshihito Shirai (Department of Biochemical Engineering and Science, Kyushu Institute of Technology, Iizuka, Fukuoka, Japan) for his advice, guidance and help.

To my colleagues; Miss Nor 'Aini, Jame'ah Hamed, Ong Ming Hooi, Norrizan Abdul Wahab, Hafizah Kassim, Manisya Zauri, Mr. Abdul Rahman Abdul Razak, Zainal Baharum, Sim Kean Hong, Cheong Weng Chong, and laboratory staff; Mr. Rosli Aslim, Mrs. Renuga a/p Panjamurti, Mrs. Latifah Hussein and Mrs. Aluyah Marzuki, thank you for your help and cooperation. A word of thanks is conveyed to my friends from Kyushu Institute of Technology who had assisted me during my experiment work in Japan.

I would like to acknowledge the financial support from IRPA (Ministry of Science, Technology and Environment, Malaysia), NEDO (Ministry of International Trade and Industry, Japan) and JSPS (Japan Society for the Promotion of Science) which had invited me to join the research program in Kyushu Institute of Technology, Iizuka for six months.



A special thanks to my beloved parents and two younger sisters, Wai San and Mei Ting, for their love and encouragement. To Kum Cheng, thank you for your support, help, advice and patience throughout my study. Last but not least, to my friends, Peck Toung, Voon Hoe, Kum Cheng's family members, who had done much to support and help towards the success of this project. Thank you. Acknowledgement is also due to all those involved directly or indirectly in the completion of this study.

I certify that Examination Committee met on 9th February 2001 to conduct the final examination of Phang Lai Yee on her Master of Science thesis entitled "Continuous Production of Organic Acids From Palm Oil Mill Effluent And Kitchen Garbage" in accordance with Universiti Pertanian Malaysia (Higher Degree) Act 1980 and Universiti Pertanian Malaysia (Higher Degree) Regulations 1981. The Committee recommends that the candidate be awarded the relevant degree. Members of the Examination Committee are as follows:

BADLISHAH SHAM BAHARIN

Associate Professor

Department of Biotechnology,
Faculty of Food Science and Biotechnology,
Universiti Putra Malaysia
(Chairman)

MOHD. ALI HASSAN, Ph.D.

Associate Professor

Department of Biotechnology,
Faculty of Food Science and Biotechnology,
Universiti Putra Malaysia
(Member)

MOHAMED ISMAIL ABDUL KARIM, Ph.D.


Professor

Department of Biotechnology,
Faculty Food Science and Biotechnology,
Universiti Putra Malaysia
(Member)

ARBAKARIYA ARIFF, Ph.D.

Associate Professor

Department of Biotechnology,
Faculty of Food Science and Biotechnology,
Universiti Putra Malaysia
(Member)




MOHD. GHAZALI MOHAYIDIN, Ph.D.

Professor

Deputy Dean of Graduate School
Universiti Putra Malaysia

Date: 21 MAR 2001

This thesis submitted to the Senate of Universiti Putra Malaysia has been accepted as fulfilment of the requirement for the degree of Master of Science.



MOHD. GHAZALI MOHAYIDIN, Ph.D.

Professor


Deputy Dean of Graduate School

Universiti Putra Malaysia

Date:

DECLARATION

I hereby declare that the thesis is based on my original work except for the quotations and citations, which have been duly acknowledged. I also declare that it has not been previously or concurrently submitted for any other degree at UPM or other institutions.



Name: Phang Lai Yee

Date: 18.03.2001

TABLE OF CONTENTS

	Page
DEDICATION	ii
ABSTRACT	iii
ABSTRAK	v
ACKNOWLEDGEMENTS	vii
APPROVAL SHEETS	ix
DECLARATION FORM	xi
LIST OF TABLES	xv
LIST OF FIGURES	xvii
LIST OF PLATES	xix
LIST OF ABBREVIATIONS	xx
CHAPTER	
I INTRODUCTION	1
II LITERATURE REVIEW	6
Palm Oil Mill Effluent (POME)	6
Anaerobic Process	9
Biochemistry	9
Microbiology	12
Acidogenesis	17
Catabolism of Polysaccharides	17
Catabolism of Lipid and Protein	19
Pathway of Lactic Acid Synthesis	20
Mode of Bioreactor Operation	23
Continuous Process	23
Continuous Process with Cell Recycle System	25
Factors Affecting Process	26
Nutrients	26
Effect of pH	27
Effect of Temperature	29
Dilution Rate and Retention Time	31
Waste Materials as Fermentative Substrate	33
Freezing and Thawing	37
Introduction	37
Sludge Freezing	38
Conceptual Model	40
Economic Potential of Acetic Acid	43
Introduction	43
Production Technologies	44
Current Uses and Potential Products	45
Economic Potential of Lactic Acid	48
Introduction	48
Manufacturing Technologies	48
Current Uses and Potential Products	51



III	GENERAL MATERIALS AND METHODS	54
	Source of Substrates	54
	Palm Oil Mill Effluent (POME)	54
	Kitchen Garbage	55
	Microorganisms and Preparation	56
	POME Sludge	56
	<i>Lactobacillus rhamnosus</i> Inoculum	56
	Preparation of <i>Lactobacilli</i> Broth	56
	Chemical Reagents	57
	Experimental Design	58
	Anaerobic Treatment of POME	58
	Fermentation of Kitchen Garbage for Lactic Acid	
	Production	59
	Analytical Methods	63
	Organic Acids Determination	63
	COD Analysis	63
	Total Solids and Volatile Solids Measurements	64
	Suspended Solids Measurement	65
	Total Kjeldahl Nitrogen Analysis	65
	Determination of Total Microbial, <i>Lactobacillus</i> and	
	<i>Clostridium</i> Populations	66
	Total Sugars Measurement	68
	Glucose Analysis	68
	D-form and L-form Lactic Acid Analysis	69
IV	ORGANIC ACIDS PRODUCTION FROM PALM OIL	
	MILL EFFLUENT	71
	Introduction	71
	Materials and Methods	72
	Chemicals, POME and Sludge	72
	Effect of Neutralizers on Anaerobic Treatment of	
	POME	72
	Continuous Anaerobic Treatment with Sludge Recycle	
	System	73
	Freezing and Thawing Technique	74
	Analyses	75
	Results	75
	Effect of Neutralizers on Anaerobic Treatment of	
	POME	75
	Anaerobic Treatment of POME with Sludge Recycle	
	System	76
	Effectiveness of the Freezing-Thawing Method	77
	Discussion	85
	Effect of Neutralizer	85
	Anaerobic Treatment of POME with Sludge Recycle	
	System	86
	Effectiveness of the Freezing-Thawing Method	89
	Conclusions	92

V	FERMENTATION OF KITCHEN GARBAGE FOR LACTIC ACID PRODUCTION.....	94
	Introduction	94
	Materials and Methods	97
	Microorganism	97
	Fermentation Substrates Preparation	97
	Continuous Fermentation	98
	Analytical Methods	99
	Results	99
	Discussions	106
	Conclusions	112
VI	SUMMARY, CONCLUSIONS AND SUGGESTIONS FOR FUTURE WORKS	114
	Summary	114
	Conclusions	117
	Suggestions	119
	REFERENCES	122
	APPENDICES	134
	BIODATA OF THE AUTHOR	139

LIST OF TABLES

Table	Page
2.1 Characteristics of palm oil mill effluent (POME)	8
2.2 Parameter limits for watercourse discharge for palm oil mill effluent	8
2.3 Non-methanogenic bacteria	13
2.4 Genera of fungi detected in digesting or drying sludges	14
2.5 Types species of methanogenic bacteria	16
2.6 Acetic acid end-use applications	46
2.7 Lactic acid: potential products and volumes	53
3.1 Characteristics of POME used in this study	54
3.2 Composition of standard kitchen garbage	55
3.3 Procedure for D-form and L-form lactic acid determination	70
4.1 Effect of neutralizers on organic acids production in continuous anaerobic treatment of POME at RT 5 days	76
4.2 Characteristics of influent, effluent, clarified solution, POME sludge and recycle sludge (in gel form) during steady-state of POME treatment at 3.5 days retention time with pH 5.0	83
4.3 Comparison of average steady state values of organic acids at 5 days RT, with that at 3.5 days RT with sludge recycle system ...	87
4.4 Doubling time and specific growth rate of acid producing bacteria and methanogenic bacteria	88
5.1 Composition of standard kitchen garbage	97
5.2 Experimental conditions and parameters for continuous fermentation of standard kitchen garbage	98
5.3 <i>Lactobacillus</i> , total microbes and <i>Clostridium</i> populations of fermentation at pH 6.8 with RT 5 days	104
5.4 <i>Lactobacillus</i> and total microbial populations of fermentation at pH 5.5 with RT 5 days	104

5.5	<i>Lactobacillus</i> and total microbial populations of fermentation at pH 5.5 with RT 2.5 days	104
5.6	D, fermentation at pH 6.8 with RT 5 days	105
5.7	D, fermentation at pH 5.5 with RT 5 days	105
5.8	D, fermentation at pH 5.5 with RT 2.5 days	105
5.9	Compiled data on lactic acid yield for continuous fermentation ..	111

LIST OF FIGURES

Figures	Page
2.1 Schematic flow diagram of a palm oil mill and the actual quantity of mill effluent	7
2.2 Anaerobic digestion of organic compounds	11
2.3 Catabolism of carbohydrates	18
2.4 Enantiomers of lactic acid	20
2.5 Schematic presentation of the main pathways of hexose fermentation in lactic acid bacteria	22
2.6 Floc schematic	39
2.7 Progression of freezing	42
2.8 Vertical migration of particles in front of a freezing plane	43
2.9 Polymerization of lactic acid	53
3.1 Experimental design for anaerobic treatment of POME	60
3.2 Experimental design for kitchen garbage fermentation for lactic acid production	62
4.1 Anaerobic treatment of POME at pH 5.0-5.5 with sludge recycle (RT 3.8 ± 0.3 days)	77
4.2 Organic acids profile for anaerobic treatment of POME at 3.5 days retention time with sludge recycle system at pH 5.0	78
4.3 Total and suspended solids profile before and after freeze/thaw treatment during steady-state of POME treatment	80
4.4 Total Kjeldahl nitrogen of effluent and clarified solution and total microbial population profile during steady-state of POME treatment	81
4.5(a) Material balance for total solids and suspended solids	82
4.5(b) Material balance for total Kjeldahl nitrogen	82
4.6(a) Concentrations change of organic acids in the fractionation of treated effluent after freeze/thaw treatment	84
4.6(b) Changes of total and suspended solids profile for each fraction ...	85

5.1(a) Organic acids profile of kitchen garbage fermentation at pH 6.8 with RT 5 days	101
5.1(b) Glucose and total sugars of kitchen garbage fermentation at pH 6.8 with RT 5 days	101
5.2(a) Organic acids profile of kitchen garbage fermentation at pH 5.5 with RT 5 days	102
5.2(b) Glucose and total sugars of kitchen garbage fermentation at pH 5.5 with RT 5 days	102
5.3(a) Organic acids profile of kitchen garbage fermentation at pH 5.5 with RT 2.5 days	103
5.3(b) Glucose and total sugars of kitchen garbage fermentation at pH 5.5 with RT 2.5 days	103

LIST OF PLATES

Plates	Page
3.1 Bioreactor set-up for anaerobic treatment of POME	61
4.1 The sludge gel after thawing	79

LIST OF ABBREVIATIONS

AN	-	Ammoniacal nitrogen
BOD	-	Biological oxygen demand
C/N	-	Carbon to nitrogen ratio
CaCO ₃	-	Calcium carbonate
CMA	-	Calcium magnesium acetate
COD	-	Chemical oxygen demand
COD/N	-	Chemical oxygen demand to nitrogen ratio
COD/P	-	Chemical oxygen demand to phosphorus ratio
CODsol	-	Soluble chemical oxygen demand
CODtot	-	Total chemical oxygen demand
D	-	Dilution rate
D(-)-LDH	-	D(-)-lactate dehydrogenase
HPLC	-	High performance liquid chromatography
HRT	-	Hydraulic retention time
I	-	Iodide
MeI	-	Methyl iodide
MeOH	-	Methanol
NaOH	-	Sodium hydroxide
NH ₄ OH	-	Ammonium hydroxide
POME	-	Palm oil mill effluent
Rh	-	Rhodium
RT	-	Retention time
SRT	-	Solid retention time

SS	-	Suspended solids
TKN	-	Total Kjeldahl nitrogen
TN	-	Total nitrogen
TS	-	Total solids
t_d	-	Doubling time
VS	-	Volatile solids
μ	-	Specific growth rate

CHAPTER I

INTRODUCTION

Anaerobic treatment process has long been popular in the wastewater treatment field. However, it has been mainly employed to stabilize the suspended organic material and to provide a source of energy. Accordingly, large amount of literature materials exists on the anaerobic digestion, most of it dealing with the overall rate-limiting methanogenic phase. Less attention has been paid to the acid phase, the process by which waste particulates are solubilized and fermented to volatile acids.

It was reported that the volatile fatty acids (VFA's) produced during anaerobic digestion of sludge have ten times commercial value than the methane produced subsequently (Jones, 1986). Volatile fatty acids such as acetic acid, lactic acid, propionic acid and higher acids could be used as chemical feedstocks. Besides, petroleum-based feedstocks have reached such high prices that interest is increasing in the bioconversion of renewable materials to replace fossil raw materials as a source of the oxychemicals feedstocks production, such as acetic acid. Thus, controlled biochemical production has attractive economic incentives associated with it.

Acetic acid is one such compound that is used extensively as an intermediate in manufacturing vinyl acetate, cellulose acetate, dimethyl terephthalate,

chloroacetic acid and various acetate esters. Demand for acetic acid is forecast to increase nearly 2% per annum to 4.2 billion pounds in the year 2004, valued at \$ 1.1 billion (USADATA, 2000). A newer industrial use of acetic acid is to produce acetate deicers, including calcium magnesium acetate (CMA) as a noncorrosive road deicer (Huang, 1998) and potassium acetate and sodium acetate as airport runway deicers. These acetate deicers are environmentally friendly.

There is also increased interest in lactic acid production due to its wide range of application areas (food, pharmaceutical, plastic, textile industry, etc). As an example, biodegradable plastics made of poly(lactic) acid have the potential to greatly expand the market for lactic acid due to the environmental issue of plastic wastes disposal.

In wastewater treatment applications, these soluble organic products from acidogenic activity can be used as energy and carbon sources for microorganisms carrying out other processes, such as biological phosphorus removal or 2-stage biological nitrogen removal (Barnard, 1983).

Waste materials generally require treatment before being discharged to the environment. This is mainly due to its polluting characteristic, i.e. high BOD value. The BOD can be a good source of raw material for biological processes if optimum operation conditions are applied. Utilization of waste materials in fermentation process is based on the concept of resource recovery and utilization while still achieving the objective of pollution control. Hence, it can be expected that producing organic acids such as acetic acid and lactic acid by the

fermentation of palm oil mill effluent and kitchen garbage or refuse will become commercially attractive.

Palm oil mill effluent (POME) has been known as the most highly polluting agro-waste in Malaysia. Rapid growth and development of palm oil industry in Malaysia has at the same time led to the production of tremendous amount of wastes. POME with its high BOD value (20,000-30,000mg/L) is commonly treated by anaerobic ponding system and open tank digesters which normally require long residence times in excess of 20 days. Recently, our research group has studied the feasibility of integrating organic acids production from POME within its conventional wastewater treatment system as part of a zero emission system for the palm oil mill (NorAini *et al.*, 1999).

Kitchen garbage or refuse is another organic substance that can be subjected to biological treatment for organic acids production, particularly for lactic acid production under controlled conditions. Kitchen garbage is a food-based material that contains carbohydrates, proteins and lipids. These compounds are essential for the growth of microorganisms to synthesize desired products. In the developed countries such as Japan, segregation of wastes according to different criteria e.g. combustible and non-combustible material, recyclable materials (bottle, cans, newsprint and paper), has been adopted in the whole country. Kitchen refuse is classified as combustible material which is usually subjected to incineration. However, owing to the environmental pollution problem, again appropriate method of handling this organic waste has to be developed.